

Material Safety Data Sheet

Powerplus Racing Fuel 98 99 100 102 105 108 110

Official Powerplus Document 2014 Edition



Contents

Section 01: **Identification of Material & Supplier**

Section 02: **Hazard Identification**

- Risk Phrases
- Safety Phrases
- Human Health Hazards
- Safety Hazards
- Environmental Hazards
- Other Information

Section 03: **Composition/Information on Ingredients**

- Preparation Description
- Chemical Name

Section 04: **First Aid Measures**

- Swallowed
- Eyes
- Skin
- Inhaled
- First Aid Facilities
- Advice to Doctor

Section 05: **Fire Fighting Measures**

- Flammability
- Suitable extinguishing media
- Hazards from combustion products
- Special protective precautions and equipment for fire fighters

Section 06: **Accidental Release Measures**

- Emergency Procedure

Section 07: **Handling and Storage**

- Handling
- Storage
- Incompatibilities
- Product Transfer
- Tank Cleaning
- Recommended Materials
- Other Information



Section 08: Exposure Controls/Personal Protection Section

Exposure Standards
Notes
Biological Limit Values
Ventilation
Special Consideration for Repair &/or Maintenance of Contaminated Equipment
Personal Hygiene
Skin Protection
Eye Protection
Respiratory Protection
Thermal Protection
Smoking & Other Dusts

Section 09: Physical and Chemical Properties

Section 10: Stability and Reactivity

Chemical Stability

Section 11: Toxicological Information

Toxicological Data
Effects Acute
Effects Chronic

Section 12: Ecological Information

Basis for Assessment
Eco-toxicity
Persistence and Degradability
Bioaccumulation
Mobility

Section 13: Disposal Considerations

Section 14: Transport Information

Section 15: Regulatory Information

Poisons Schedule

Section 16: Other Information

Contact
Australian Standards
Other References



Section 01: **Identification of Material and Supplier**

Product Name	Powerplus Racing Fuel 98, 99, 100, 102, 105, 108 & 110
Other Names	98, 99, 100, 102, 105, 108 & 110
Product Codes/Trade Names	N/A
Recommended Use	Fuel for spark ignition engines designed to run on unleaded fuel.
Applicable In:	Australia
Supplier	Powerplus
Address	118 Swann Drive, Derrimut Victoria 3030
Telephone	+61 3 93690220
Email Address	info@acbgroup.com.au
Facsimile	+61 3 93690883
Emergency Phone Number	000 Fire Brigade and Police (Available in Australia only).
Poisons Information Centre	Poisons Information Centre: 13 11 26 (Available in Australia only).

This Material Safety Data Sheet (MSDS) is issued by the Supplier in accordance with National standards and guidelines from the Australian Safety and Compensation Council (ASCC, formerly National Occupational Health and Safety Commission - NOHSC). The information in it must not be altered, deleted or added to. The Supplier will not accept any responsibility for any changes made to its MSDS by any other person or organization. The Supplier will issue a new MSDS when there is a change in product specifications and/or ASCC standards, codes, guidelines, or Regulations.

Section 02: **Hazard Identification**

Hazards Identification	HAZARDOUS SUBSTANCE. DANGEROUS GOODS. Hazard classification according to the criteria of NOHSC. Dangerous goods classification according to the Australia Dangerous Goods Code.
-------------------------------	--

Risk Phrase

R12:	Extremely flammable
R45	May cause cancer
R46	May cause heritable genetic damage
R38	Irritating to skin
R63	Possible risk of harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R67	Vapours may cause drowsiness and dizziness
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R11	Highly flammable



Safety Phrases

S16	Keep away from sources of ignition - No smoking.
S2	Keep out of reach of children.
S23(4)	Do not breathe vapour.
S24	Avoid contact with skin.
S29	Do not empty into drains.
S43(1)	In case of fire use alcohol resistant foam/dry powder/CO2. Never use water.
S45	In case of accident or if you feel unwell seek medical advice immediately
S53	Avoid exposure - obtain special instructions before use.
S61	Avoid release to the environment. Refer to special instructions/safety data sheet.
S62	If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Human Health Hazards

Hydrocarbon Components: May cause cancer. Product classified as a Category 2 carcinogen. May cause heritable genetic damage. Product classified as a Category 2 mutagen. Possible risk of harm to the unborn child. Product is classified as a Category 3 Reproductive toxicant. Irritating to skin. Harmful, may cause lung damage if swallowed. Aspiration into the lungs may cause chemical pneumonitis which can be fatal. Vapours may cause drowsiness and dizziness. This product contains benzene, which is known to cause leukaemia and n-hexane, which has been shown to metabolize to compounds which are neuropathic. This product contains toluene. There are indications from animal studies that prolonged exposure to high concentrations of Toluene may lead to hearing loss.

Safety Hazards

Extremely flammable. Risk of generating electrostatic charges during handling. Liquid evaporates quickly and can ignite leading to a flash fire, or an explosion in a confined space.

Environmental Hazards

Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Unlike other gasoline components, ethanol is miscible with water.

Other Information

This product is intended for use as a fuel in a closed system. If used for any other purpose, in open systems or as a spray, ignition and exposure risks will increase and a careful risk assessment should be carried out.



Section 03: **Composition/Information on Ingredients**

Preparation Description

Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons (Including benzene at 1.0%v/v maximum), with carbon numbers predominantly in the C4 to C12 range. Contains oxygenated hydrocarbons, including ethanol or other alcohols. May also contain several additives at <0.1% v/v each. Dyes and markers can be used to indicate tax status and prevent fraud.

Chemical Name	Synonyms	Proportion	CAS Number:
Gasoline low boiling point naptha	-	99.7%-100%	86290-81-5
Antioxidants, corrosion inhibitors, metal deactivators, dyes and proprietary performance improving packages.	-	0-15%	Mixture
Ethanol	-	0-9%	64-17-5

Section 04: **First Aid Measures**

If poisoning occurs, contact a doctor or Poisons Information Centre.

Swallowed

DO NOT INDUCE VOMITING. Protect airway if vomiting begins. Give nothing by mouth. If breathing but unconscious, place in recovery position. If breathing has stopped, apply artificial respiration. OBTAIN MEDICAL ATTENTION IMMEDIATELY.

Eyes

Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

Skin

Wash skin with water using soap if available. Note that contaminated clothing may be a fire hazard. Contaminated clothing should be soaked with water before being removed. It must be laundered before reuse. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.

Inhaled

Remove to fresh air. If breathing but unconscious, place in the recovery position. If breathing has stopped, apply artificial respiration. If heartbeat absent, give external cardiac compression. Monitor breathing and pulse. Seek urgent medical advice.



First Aid Facilities

First aid kits, safety showers, eye wash stations.

Advice to Doctor

Treat symptomatically. In cases of ingestion, consider gastric lavage. Gastric lavage must only be undertaken after cuffed endotracheal intubation in view of the risk of aspiration. Administration of carbon for medicinal use (carbo medicinalis) may reduce absorption from the digestive tract. In cases of chemical pneumonitis, antibiotic and corticosteroid therapy should be considered, but only under expert guidance and with special care facilities. High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimize tissue damage and loss of function.

Section 05: Fire Fighting Measures

Flammability

Product is Highly Flammable. Isolate from sources of heat, naked flames, sparks and oxidising materials. Take precautions against discharges of static electricity Earth and bond all process equipment including tanks and drums. Ensure ventilation is adequate to prevent build up of explosive atmosphere. Refer to AS 1940 - Storage and handling of flammable and combustible liquids and AS 2865 - Safe working in a confined space, for more specific information on these subjects.

Suitable extinguishing media

Use foam, CO2 or powder to extinguish fire.

Hazards from combustion products

Combustion products include oxides of carbon.

Special protective precautions and equipment for fire fighters

Flammable liquid. Keep storage tanks, pipelines, fire exposed surfaces etc. cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively and flashback along the vapour trail may occur. Highly flammable liquid. Use water to cool exposed containers. Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire.

Spills and leaks may be washed away with copious volumes of water, fog or spray. For major fires or where the atmosphere is either oxygen deficient or contains unacceptable levels of combustion products, fire fighters must wear self contained breathing apparatus with full face-mask and protective clothing.



Section 06: **Accidental Release Measures**

Emergency Procedure

Wear appropriate personal protective equipment. Extinguish or remove all sources of ignition and stop leak if safe to do so. Contain the spill with sand or earth and take up with a vacuum truck or absorb with absorbent material, sand or earth. Keep away from heat, naked flames and sparks. Place used absorbent in suitable sealed containers for disposal.

Section 07: **Handling and Storage**

Handling

Never siphon by mouth. When using do not eat, drink or smoke. Avoid contact with skin, eyes and respiratory system. If using pressurised equipment, take extra care to avoid injection under the skin. Only use in well ventilated areas. Take precautionary measures against static discharges. Ensure all equipment is properly earthed. Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Prevent spillages. Cloth, paper and other materials that are used to absorb spills present a fire hazard. Avoid their accumulation by disposing of them safely and immediately. In addition to any specific recommendations given for controls of risks to health, safety and the environment, an assessment of risks must be made to help determine controls appropriate to local circumstances.

Storage

This product must never be stored in buildings occupied by people. Small volumes (maximum 5 litres), may be stored in a suitably designed portable container. Such containers should be stored in well-ventilated areas, flame proof cabinets or stores. Use properly labelled and closable containers. Keep container tightly closed in a dry, well-ventilated place away from direct sunlight and other sources of heat or ignition. Take suitable precautions when opening sealed containers, as pressure can build up during storage. Keep in a bundled area with a sealed (low permeability) floor, to provide containment against spillage. Prevent ingress of water. Stack drums to a height not exceeding 3 metres without the use of racking. Locate tanks away from heat and other sources of ignition. Seek specialist advice for the design, construction and operation of bulk storage facilities.

Incompatibilities

Synthetic materials such as plastics and fibreglass may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are:



natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene. However, some may be suitable for glove materials.

Product Transfer

Electrostatic charges may be generated during pumping. Ensure electrical continuity by bonding all equipment. Avoid splash filling. Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes.

Tank Cleaning

Cleaning, inspection and maintenance of storage tanks is a specialist operation that requires the implementation of strict procedures and precautions. These include issuing of work permits, gas freeing of tanks, using a manned harness, lifelines, and wearing air-supplied breathing apparatus. Prior to entry and whilst cleaning is underway, the atmosphere within the tank must be monitored using an oxygen meter and explosimeter. Additional precautions are required where the tank may previously have contained leaded gasoline.

Recommended Materials

For containers or container linings, use mild steel or stainless steel. Aluminium may also be used for applications where it does not present an unnecessary fire hazard. Examples of suitable materials are: high density polyethylene (HDPE), polypropylene (PP), and Viton (FKM), which have been specifically tested for compatibility with this product. For container linings, use amineadduct cured epoxy paint. For seals and gaskets use: graphite, PTFE, Viton A, Viton B.

Other Information

Ensure that all local and international regulations regarding handling and storage facilities are followed. The following activities have been associated with high levels of exposure to gasoline vapours: Top-loading of tankers, open ship loading by deck crew, drum filling/emptying and laboratory testing (particularly sample bottle washing).

Section 08: Exposure Controls/Personal Protection

Exposure Standards

National Occupational Exposure Standard (NES) Australian Safety & Compensation Council, ASCC (formerly NOHSC)
Powerplus Racing Fuel
Ethanol in Powerplus Racing Fuel
TWA - 1000 ppm (1880 mg/m³)

[NOHSC:1003(1995)] - 3rd Edition



Notes

All occupational exposures to atmospheric contaminants should be kept to as low a level as is workable (practicable) and in all cases to below the National Standard. These Exposure Standards are guides to be used in the control of occupational health hazards.

These Exposure Standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

TWA (Time Weighted Average): the time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers. STEL (Short Term Exposure Limit): the average airborne concentration over a 15 minute period that should not be exceeded at any time during a normal eight hour work day.

Biological Limit Values

N/A

Ventilation

The level of personal protection and the types of controls necessary will vary depending on exposure conditions. Select controls based on a risk assessment of local circumstances. Use sealed systems as far as possible. Use local, intrinsically safe, exhaust ventilation if there is a risk of inhalation of vapours, mists, or aerosols. Provide eye washes and showers for emergency use.

Special Consideration for Repair &/or Maintenance of Contaminated Equipment

Empty containers retain residue (liquid and/or vapour) and are dangerous. Do not pressure cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

Vapour is heavier than air – prevent concentration in hollows or sumps. Do not enter confined spaces where vapour may have collected. Keep containers closed when not in use.

Personal Hygiene Body Protection

Minimise all forms of skin contact. In the event of risk from splashing wear e.g. Nitrile, PVC, or neoprene rubber apron. Wear safety shoes or boots which are chemical and petroleum distillate resistant.

Skin Protection

Select gloves tested to a relevant standard (e.g. Europe EN374, US F739). When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes). For incidental contact/splash protection Neoprene or PVC gloves may be suitable. Breakthrough times for gloves varies depending on, e.g. chemical resistance, material thickness, frequency and duration of contact. Selection should also take into account other usage requirements, e.g. dexterity, heat resistance, other chemical substances handled. Always seek advice from glove suppliers. Contaminated gloves should be



replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Eye Protection

Wear safety glasses or full face shield if splashes are likely to occur.

Respiratory Protection

Care should be taken to keep exposures below applicable occupational exposure limits. If this cannot be achieved, use of a respirator fitted with an organic vapour cartridge combined with a particulate pre-filter should be considered. Where air filtering respirators are unsuitable (e.g. where airborne concentrations are high, there is a confined space or a risk of oxygen deficiency) use appropriate positive pressure breathing apparatus.

Thermal Protection

None should be needed under normal circumstances.

Smoking & Other Dusts

Smoking must be prohibited in all areas where this product is used - see safety information on flammability.

Section 09: Physical and Chemical Properties

Appearance	Mobile clear colourless liquid/ pale straw/ yellow.
Odour	Characteristic
pH, at stated concentration	N/A
Vapour pressure	30 to 90 kPa at 20°C. Vapour pressure is often determined by legislation, and varies with season
Vapour Density	> 3 (Air = 1)
Boiling Point (°C)	Initial - 25°C circa Final - 215°C circa
Freezing/Melting Point (°C)	No data available.
Solubility	Partly soluble due to the content of oxygenated components.
Specific Gravity (H₂O = 1)	720 to 775 kg/m ³ at 15°C.
Flash Point	<-40°C (Method: PMCC).
Flash Point Method	PMCC
Flammable (Explosive)	6-8%(V/V) maximum.
Limit - Upper	
Flammable (Explosive)	1%(V/V) minimum.
Limit - Lower	
Auto ignition Temperature	>250°C.
Evaporation Rate	No data available.
Volatile Organic Compounds Content (VOC)	(as specified by the Green Building Council of Australia) Not
% Volatiles	No data available.



Section 10: **Stability and Reactivity**

Chemical Stability

Stable. Avoid strong oxidising agents.

Section 11: **Toxicological Information**

Toxicological Data

Health effects information is based on reported effects in use from overseas and Australian reports.

Effects Acute Swallowed

Harmful. May cause lung damage if swallowed.

Eyes

Mildly irritating to the eyes.

Skin

Irritating to skin. Will cause redness and inflammation.

Inhaled

Inhalation may cause irritation to the respiratory system. Prolonged exposure to vapours may cause somnolence and narcosis.

Effects Chronic

Prolonged and repeated skin contact may cause dermatitis due to defatting effect. Prolonged or repeated exposure may cause cancer.

Section 12: **Ecological Information**

Basis for Assessment

Fuels are typically made from blending several refinery streams. Ecotoxicological studies have been carried out on a variety of hydrocarbon blends and streams but not those containing additives. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Eco-toxicity

Product is classified as toxic to aquatic organisms, LL/EL50 1 -10 mg/l. (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Films formed on water may affect oxygen transfer and damage organisms.

Persistence and Degradability

Major components are inherently biodegradable. Persists under anaerobic conditions. The volatile components oxidise rapidly by photochemical reactions in air.

Bioaccumulation

Contains components with the potential to bioaccumulate.

Mobility

Floats on water. Contains volatile components. Evaporates within a day from water or soil surfaces. Large volumes may penetrate soil and could contaminate groundwater.



Section 13: **Disposal Considerations**

Follow state or local authority regulations and guidelines for disposal of the waste. Clean area with detergent and water - do not allow product to enter drains, sewers or water courses- inform the local authorities if this occurs.

Section 14: **Transport Information**

Proper Shipping Name	PETROL
UN number	1268
DG Class	3
Subsidiary Risk 1	None Allocated
Packaging Group	II
HAZCHEM code	3YE
Packaging Method	3.8.3
EPG Number 3.1.001	3.1.001
IERG Number	14
Marine Pollutant	No
Special Precautions	Refer to incompatibilities in section 7 and stability and reactivity information in section 10.
Additional transport requirements	Nil

Section 15: **Regulatory Information**

Poisons Schedule S5

Section 16: **Other Information**

Contact	ACB Group (ABN 79 724 186 134) 118 Swann Drive, Derrimut Victoria-3030, Australia. Phone: +61 3 93690220 Fax: +61 3 93690883
AS1020 AS1076	The Control of undesirable static electricity. Code of Practice for selection, installation and maintenance of electrical apparatus and associated equipment for use in explosive atmospheres (other than mining applications) – Parts 1 to 13.
AS/NZS 1336 AS/NZS 1715	Recommended Practices for Occupational Eye Protection Selection, Use and Maintenance of Respiratory Protective Devices
AS/NZS 1716 AS 1940	Respiratory Protective Devices The Storage and Handling of Flammable and Combustible Liquids.
AS 2161	Industrial Safety Gloves and Mittens (excluding electrical and medical gloves)



Powerplus is a trade mark of ACB Group Pty Ltd 118 Swann Drive, Derrimut 3030 Victoria. Australia.
Ph: 03 9369 0220 Fax: 03 9369 0883 www.powerplusfuel.com.au

MSDS: COOGEE RESEARCH BLENDS. DATE ISSUED : 07 MARCH 2013

AS2380	Electrical equipment for explosive atmospheres – Explosion Protection Techniques (Parts 1 to 9).
AS3000	Electrical installations (known as the Australian/New Zealand Wiring Rules).
NOHSC:2011(2003)	National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition, April 2003, National Occupational Health and Safety Commission.
NOHSC; 2012 (1994)	National Code of Practice for the Labelling of Workplace Substances, March 1994, Australian Government Publishing Service, Canberra.
NES	National Occupational Exposure Standards for workplace Atmospheric Contaminants (NES) Australian Safety and Compensation Council, ASCC (Formerly NOHSC) 1995 as amended.
ADG Code 6th Edition	Australian Dangerous Goods Code 6th Edition

Authorisation

Reason for Issue: 5 year review
 Authorized by: ACB Technical Director
 Date of Issue: 21 September 2010
 Expiry Date: September 2015

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of this information.

